

## P 产品介绍

Product Introduction

GPT300

400

## P 产品特点

Product Features

- ◆  $\pm 1.0\%$
- ◆
- ◆ Tin TiAlN
- ◆
- ◆ 0~ 35 to 0-2000bar / 0~ 500 to 0~ 30000psi
- ◆ 4~ 20mA 0~ 20mA 0~ 10v 0~ 5V
- ◆ 400
- ◆
- ◆ 1/2~ 20UNF M18\*1.5, M22\*1.5,



## S 技术参数

Specification

项目	参数	
	0~ 35 to 2000bar(0~ 500 to 0~ 30000psi)	
	$\pm 1\%$ FS	
	$\pm 0.8\%$ FS	
	24VDC 9~ 36VDC	10 VDC 12 VDC
	4~ 20mA, 0~ 20mA, 0~ 10V, 0~ 5V, 1~ 5V	2.0mV/V for 5PIN, 3.33mV/V for 6PIN
	662°F (350 )	
	752°F (400 )	
	40 psi/100 0.3MPa/100	
	1/2-20 UNF (45° ) M14x1.5, M18x1.5, M22x1.5 etc	
	1.5 x FSO	
	PSI, Bar, Mpa or Kg/cm <sup>2</sup>	
	80% FSO	
	5PIN or 6PIN	
( )	E, J, K, S type or Pt100	

## T 产品选型 Type selection

GPT300	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	选型说明
A								
B								
C								
								0~ 5 to 200Mpa / 0~ 35 to 2000bar / 0~ 500 to 30000psi
		T1						4~ 20mA (
		T2						0~ 20mA (
		T3						0~ 10V (
		T4						0~ 5V (
		T5						1~ 5V (
		T6						2.0mV/V , 5PIN
		T7						3.33mV/V, 6PIN
		V1						24VDC (
		V2						9~ 36VDC (
		V3						10 VVDC
		V4						12 VVDC
		C1						1/2-1/2-20UNF
		C2						M14= M14*1.5
		C3						M18= M18*1.5
		B1						5 pin
		B2						6 pin
		L1						: 150mm
		L2						: 470mm
								J,K,E PT100